

1799 **Annex 3. Factory Class Competition**

1800 A factory rifle is defined as any standard production rifle - not a custom shop rifle – with a
1801 Manufacturer’s Suggested Retail Price (MSRP) maximum of \$2000.

1802
1803 For 600-Yard and 1000-Yard Factory Class competitions, the rifle and rests must conform to the
1804 following rules:
1805

- 1806 • Commercial bolt action - commercially produced rifle, using the commercially installed
1807 action, factory installed barrel, and factory stock. A new barrel may be installed provided
1808 it is done by the factory who manufactured the rifle
- 1809 • Must be fired single shot.
- 1810 • No stock modifications except that the action and breech end of the barrel may be bedded
1811 • and up to 2 inches of the breech end of the barrel may be glass bedded.
- 1812 • Any safe trigger may be installed in the rifle
- 1813 • Any scope may be used.
- 1814 • Front rests may be used provided the rifle stock has not been modified or augmented in
1815 any way where the stock contacts the front rest. No one-piece rests.
- 1816 • Monopods and Bipods are legal; in which the fore-end of the stock may be modified.
- 1817 • A rear sand bag and front pedestal authorized
- 1818 • No mechanical rear rests. Rear rests must be a sandbag type rear rest.
- 1819 • Sling swivels and sling swivel screws may be removed from the stock
- 1820 • Maximum rifle weight is 17 pounds, weighed in the as-fired configuration, including any
1821 bipod or monopod.
- 1822 • No modification of the factory action or factory barrel may be made, except that a muzzle
1823 brake may be installed. The barrel may be removed from the action to thread and install
1824 the muzzle brake. Head spacing may not be changed from the factory head spacing.
- 1825 • The action/barrel may not be re-chambered or be modified in any way.
- 1826 • Silencers, suppressors, or other components may not be added to the as-produced factory
1827 configuration unless specifically noted above.
- 1828 • A tied-on or taped-on cheek riser may be used.
- 1829 • One layer of bench rest stock tape may be installed on the fore end and toe end of the
1830 stock.
- 1831 • A bag rider may be installed on the butt stock of a chassis rifle.

1832
1833
1834
1835 Except as noted above or specifically noted in the rules for 1000-yard competition for factory
1836 class the rules for factory class for 1000-yard competition are the same as defined for Light Gun.

1837

1838 Except as noted above or specifically noted in the rules for 600-yard competition for factory
1839 class the rules for factory class for 600-yard competition are the same as defined for Light Gun.

1840